

- 1 Item 448 1 1/2" Asphalt Concrete, Surface Course, Type I, PG64-22, Medium Traffic
- (2) Item 448 2 1/2" Asphalt Concrete\*, Intermediate Course, Type 2, PG64-22, Medium Traffic
- 3 Item 304 6" Aggregate Base
- (4) Item 204 Subgrade Compaction
- (5) Item 659 Seeding & Mulching, As Per Plan
- 6 ltem 653 3" Min pulverized topsoil, furnished & placed, As Per Plan or approved equal
- Item 407 Tack coat, type and rate as directed by the engineer. May be omitted if surface course is applied immediately following intermediate course of asphalt
- (a) Side slopes per typical section of plan
  - All seeding/mulching and topsoil shall be free of weeds to ensure quality growth of grass
- (b) For multi—use paths, 12' in width or greater, consideration should be given to provide a center crown
  - \* Note: Asphalt concrete intermediate course may be reduced to 1½" min. in locations where utility, maintenance, or construction vehicle use of the path is expected to be minimal. City Engineer approval is required for this reduction.

		CITY OF	
	MULTI-USE PATH DETAILS	HILLIARD, OHIO	
DATE: July 29, 2016	MOLII-USE PAIR DETAILS	STANDARD CONSTRUCTION DRAWING	
SCALE: 1" = 2'		1/1	BP-1